
Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Helium

Issue date: 03/06/2016 SDS reference: LIT-He-061A Supersedes: 03/03/2017

Revision date: 02/01/2020

Version: 2.1



SECTION 1: Identification of the substance/mixture and of the company/undertaking

Trade name	: Helium
SDS no	: LIT-He-061A
Chemical description	: Helium
	CAS-No. : 7440-59-7
	EC-No. : 231-168-5
	EC Index-No. :
Registration-No.	: Listed in Annex IV / V REACH, exempted from registration.
Chemical formula	: He
1.2. Relevant identified uses of th	e substance or mixture and uses advised against
Relevant identified uses	: Industrial and professional uses. Perform risk assessment prior to use
	Test gas/Calibration gas.
	Purge gas, diluting gas, inerting gas.
	Purging.
	Laboratory use.
	Use for manufacture of electronic/photovoltaic components.
	Shield gas for welding processes.
	Contact supplier for more information on uses.
Uses advised against	: Do not inhale product on purpose because of the risk of asphyxiation.
1.3. Details of the supplier of the	safety data sheet
Company identification	: Elme Messer Lit
	Ateities g.10 B-1 LT-08303 Vilnius - Lietuva
	www.elmemesser.lv
	vilnius@elmemesser.lv

1.4. Emergency telephone number

Emergency telephone number

ELME MESSER G/4/S

: Apsinuodijimų tarnybos pagalbos telefonas - +370 5 236 20 52, 24 valandas per parą

H280

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]		
Physical hazards	Press. Gas (Comp.)	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

ELME MESSER G44S	Helium
	SDS Ref.: LIT-He-061A
Hazard pictograms (CLP)	GHS04
Signal word (CLP)	: Warning
Hazard statements (CLP)	: H280 - Contains gas under pressure; may explode if heated.
Precautionary statements (CLP)	
	- Storage : P403 - Store in a well-ventilated place.
Supplemental information	: Do not inhale product on purpose because of the risk of asphyxiation.
2.3. Other hazards	: Asphyxiant in high concentrations.

SECTION 3: Composition/information on ingredients

3.1. Substances

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Helium	(CAS-No.) 7440-59-7 (EC-No.) 231-168-5 (EC Index-No.) (Registration-No.) *1	100	Press. Gas (Comp.), H280

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

*3: Registration not required: Substance manufactured or imported < 1t/y.

3.2. Mixtures : Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation	: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.		
- Skin contact	: Adverse effects not expected from this product.		
- Eye contact	: Adverse effects not expected from this product.		
- Ingestion	: Ingestion is not considered a potential route of exposure.		
4.2. Most important symptoms and effects, both acute and delayed			
	 In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. 		
	Refer to section 11.		

4.3. Indication of any immediate medical attention and special treatment needed

: None.

ELME MESSER G/4/AS

Helium

SDS Ref.: LIT-He-061A

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
- Suitable extinguishing media	: Water spray or fog.
- Unsuitable extinguishing media	: Do not use water jet to extinguish.
5.2. Special hazards arising from the substa	nce or mixture
Specific hazards	: Exposure to fire may cause containers to rupture/explode.
Hazardous combustion products	: None.
5.3. Advice for firefighters	
Specific methods	Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
	If possible, stop flow of product.
	Use water spray or fog to knock down fire fumes if possible.
	Move containers away from the fire area if this can be done without risk.
Special protective equipment for fire fighters	: Use self-contained breathing apparatus.
	In confined space use self-contained breathing apparatus.
	Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.
	Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
	Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Try to stop release.		
	Evacuate area.		
	Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.		
	Ensure adequate air ventilation.		
	Act in accordance with local emergency plan.		
	Stay upwind.		
	Oxygen detectors should be used when asphyxiating gases may be released.		
6.2. Environmental precautions			
:	Try to stop release.		
6.3. Methods and material for containment and cleaning up			
:	Ventilate area.		
6.4. Reference to other sections			
:	See also sections 8 and 13.		

SECTION 7: Handling and storage

7.1. Precautions for safe handling

ELME MESSER G44S Helium		
	SDS Ref.: LIT-He-061A	
Safe use of the product	: The product must be handled in accordance with good industrial hygiene and safety	
Sale use of the product	procedures.	
	Only experienced and properly instructed persons should handle gases under pressure.	
	Consider pressure relief device(s) in gas installations.	
	Ensure the complete gas system was (or is regularily) checked for leaks before use.	
	Do not smoke while handling product.	
	Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.	
	Do not breathe gas.	
	Avoid release of product into work area.	
	Avoid suck back of water, acid and alkalis.	
Safe handling of the gas receptacle	: Refer to supplier's container handling instructions.	
	Do not allow backfeed into the container.	
	Protect containers from physical damage; do not drag, roll, slide or drop.	
	When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.	
	Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.	
	If user experiences any difficulty operating valve discontinue use and contact supplier.	
	Never attempt to repair or modify container valves or safety relief devices.	
	Damaged valves should be reported immediately to the supplier.	
	Keep container valve outlets clean and free from contaminants particularly oil and water.	
	Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.	
	Close container valve after each use and when empty, even if still connected to equipment.	
	Never attempt to transfer gases from one cylinder/container to another.	
	Never use direct flame or electrical heating devices to raise the pressure of a container.	
	Do not remove or deface labels provided by the supplier for the identification of the content of the container.	
	Suck back of water into the container must be prevented.	
	Open valve slowly to avoid pressure shock.	
7.2. Conditions for safe storage, including	ig any incompatibilities	
	: Observe all regulations and local requirements regarding storage of containers.	
	Containers should not be stored in conditions likely to encourage corrosion.	
	Container valve guards or caps should be in place.	
	Containers should be stored in the vertical position and properly secured to prevent them from falling over.	
	Stored containers should be periodically checked for general condition and leakage.	
	Keep container below 50°C in a well ventilated place.	
	Store containers in location free from fire risk and away from sources of heat and ignition.	
	Keep away from combustible materials.	
7.3. Specific end use(s)		
	. None	
	: None.	

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL (Occupational Exposure Limits)	:	None available.
DNEL (Derived-No Effect Level)	:	None available.

ELME MESSER G/44S	Helium
	SDS Ref.: LIT-He-061A
PNEC (Predicted No-Effect Concentration)	: None available.
8.2. Exposure controls	
8.2.1. Appropriate engineering controls	
	 Provide adequate general and local exhaust ventilation. Systems under pressure should be regularily checked for leakages. Oxygen detectors should be used when asphyxiating gases may be released. Consider the use of a work permit system e.g. for maintenance activities.
8.2.2. Individual protection measures, e.g	
	: A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected.
Eye/face protection	: Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specifications.
Skin protection	
- Hand protection	 Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risk. Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
Respiratory protection	 Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
Thermal hazards	: None necessary.
8.2.3. Environmental exposure controls	: None necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

• Physical state at 20°C / 101.3kPa	: Gas
Colour	: Colourless.
Odour	: No odour warning properties.
Odour threshold	: Odour threshold is subjective and inadequate to warn of overexposure.
рН	: Not applicable.
Melting point / Freezing point	: -272 °C
Boiling point	: -269 °C
Flash point	: Not applicable for gases and gas mixtures.
Evaporation rate	: Not applicable for gases and gas mixtures.
Flammability (solid, gas)	: Non flammable.
Explosive limits	· Non flammable.
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Vapour density	: Not applicable.

ELME MESSER G/4/S

Helium

SDS Ref.: LIT-He-061A

: Not applicable.
: 0.14
: 1.5 mg/l
: Not applicable for inorganic products.
: Not applicable.
: None.
: 4 g/mol
: -268 °C
: None.

SECTION 10: Stability and reactivity

10.1. Reactivity	
	: No reactivity hazard other than the effects described in sub-sections below.
10.2. Chemical stability	
	: Stable under normal conditions.
10.3. Possibility of hazardous reactions	
	: None.
10.4. Conditions to avoid	
	: None under recommended storage and handling conditions (see section 7).
	Avoid moisture in installation systems.
10.5. Incompatible materials	
	: None.
	For additional information on compatibility refer to ISO 11114.
10.6. Hazardous decomposition products	
	: None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects		
Acute toxicity	: No known toxicological effects from this product.	
Skin corrosion/irritation	: No known effects from this product.	
Serious eye damage/irritation	: No known effects from this product.	
Respiratory or skin sensitisation	: No known effects from this product.	
Germ cell mutagenicity	: No known effects from this product.	
Carcinogenicity	: No known effects from this product.	
Toxic for reproduction : Fertility	: No known effects from this product.	
Toxic for reproduction : unborn child	: No known effects from this product.	
STOT-single exposure	: No known effects from this product.	
STOT-repeated exposure	: No known effects from this product.	
Aspiration hazard	: Not applicable for gases and gas mixtures.	

Helium

SDS Ref.: LIT-He-061A

SECTION 12: Ecological information	
<u>12.1. Toxicity</u>	
Assessment	: No ecological damage caused by this product.
EC50 48h - Daphnia magna [mg/l] EC50 72h - Algae [mg/l] LC50 96 h - Fish [mg/l]	 No data available. No data available. No data available.
12.2. Persistence and degradability	
Assessment	: No ecological damage caused by this product.
12.3. Bioaccumulative potential	
Assessment	: No ecological damage caused by this product.
12.4. Mobility in soil	
Assessment	: No ecological damage caused by this product.
12.5. Results of PBT and vPvB assessment	
Assessment	: Not classified as PBT or vPvB. No data available.
12.6. Other adverse effects	
Other adverse effects	: No known effects from this product.
Effect on the ozone layer	: None.
Effect on global warming	: None.
SECTION 13: Disposal considerations	

13.1. Waste treatment methods	
	Do not discharge into any place where its accumulation could be dangerous.
	Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at http://www.eiga.eu for more guidance on suitable disposal methods.
	May be vented to atmosphere in a well ventilated place.
	Return unused product in original container to supplier.
List of hazardous waste codes (from Commission Decision 2000/532/EC as amended)	: 16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04.
13.2. Additional information	
	: None.
	External treatment and disposal of waste should comply with applicable local and/or national regulations.
SECTION 14: Transport information	

<u>14.1. UN number</u>

UN-No.

: 1046

14.2. UN proper shipping name

ELME MESSER G/4S Helium		
		SDS Ref.: LIT-He-061A
Transport by road/rail (ADR/RID)	· HELIUM, COMPRESSED	
Transport by air (ICAO-TI / IATA-DGR)	HELIUM, COMPRESSED	
Transport by sea (IMDG)	· HELIUM, COMPRESSED	
14.3. Transport hazard class(es)		
Labelling		
Labening		
	2	
	2.2 : Non flammable, non-toxic gases.	
Transport by road/rail (ADR/RID)		
Class	: 2	
Classification code Hazard identification number	: 1A : 20	
Tunnel Restriction	: E - Passage forbidden through tunnels of category E	
Transport by air (ICAO-TI / IATA-DGR)		
Class / Div. (Sub. risk(s))	: 2.2	
Transport by sea (IMDG)		
Class / Div. (Sub. risk(s))	: 2.2	
Emergency Schedule (EmS) - Fire	: F-C	
Emergency Schedule (EmS) - Spillage	: S-V	
14.4. Packing group		
Transport by road/rail (ADR/RID)	: Not applicable	
Transport by air (ICAO-TI / IATA-DGR)	: Not applicable	
Transport by sea (IMDG)	: Not applicable	
14.5. Environmental hazards		
Transport by road/rail (ADR/RID)	. Nana	
	: None.	
Transport by air (ICAO-TI / IATA-DGR)	: None.	
Transport by sea (IMDG)	: None.	
14.6. Special precautions for user		
Packing Instruction(s)		
Transport by road/rail (ADR/RID)	: P200	
Transport by air (ICAO-TI / IATA-DGR)		
Passenger and Cargo Aircraft	: 200.	
Cargo Aircraft only	: 200.	
Transport by sea (IMDG)	: P200	

ELME MESSER GAAS	Helium	
	SDS Ref.: LIT-He-061A	
Special transport precautions	: Avoid transport on vehicles where the load space is not separated from the driver's compartment.	
	Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.	
	Before transporting product containers:	
	- Ensure there is adequate ventilation.	
	- Ensure that containers are firmly secured.	
	- Ensure valve is closed and not leaking.	
	- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.	
	- Ensure valve protection device (where provided) is correctly fitted.	
14.7. Transport in bulk according to Annex	14.7. Transport in bulk according to Annex II of Marpol and the IBC Code	
	: Not applicable.	
SECTION 15: Regulatory information	on	
15.1. Safety, health and environmental regu	lations/legislation specific for the substance or mixture	
EU-Regulations		
Restrictions on use	: None.	
Other information, restriction and prohibition regulations	: Ensure all national/local regulations are observed.	
Seveso Directive : 2012/18/EU (Seveso III)	: Not covered.	
National regulations		
No additional information available		
15.2. Chemical safety assessment		
	: A CSA does not need to be carried out for this product.	
SECTION 16: Other information		

ELME MESSER G/4/4S	Helium
	SDS Ref.: LIT-He-061A
Abbreviations and acronyms	: ATE - Acute Toxicity Estimate
, ,	CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
	REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
	EINECS - European Inventory of Existing Commercial Chemical Substances
	CAS# - Chemical Abstract Service number
	LC50 - Lethal Concentration to 50 % of a test population
	RMM - Risk Management Measures
	PBT - Persistent, Bioaccumulative and Toxic
	vPvB - Very Persistent and Very Bioaccumulative
	STOT- SE : Specific Target Organ Toxicity - Single Exposure
	CSA - Chemical Safety Assessment
	EN - European Standard
	UN - United Nations
	ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
	IATA - International Air Transport Association
	IMDG code - International Maritime Dangerous Goods
	RID - Regulations concerning the International Carriage of Dangerous Goods by Rail WGK - Water Hazard Class
	STOT - RE : Specific Target Organ Toxicity - Repeated Exposure
Training advice	: The hazard of asphyxiation is often overlooked and must be stressed during operator training.
	For more guidance, refer to EIGA SL 01 "Dangers of Asphyxiation", downloadable at http://www.eiga.eu
DISCLAIMER OF LIABILITY	: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
	Details given in this document are believed to be correct at the time of going to press.
	Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.