Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ELME MESSER G/4/S

hydrogen Issue date: 03/06/2016 SDS reference: LIT-H2-067A

Supersedes: 12/03/2019

Revision date: 12/01/2020

Version: 2.2



SECTION 1: Identification of the substance/mixture and of the company/undertaking

Trade name : hydrogen SDS no : LT-H2:067A Chemical description : hydrogen CAS-No. : 1333-74-0 EC-No.: 215-605-7 EC Index-No. : 001-001-00-9 Registration-No. Chemical formula : Listed in Annex IV / V REACH, exempted from registration. Chemical formula : Hz 12. Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use. Test gas/Calibration gas. Laboratory use. Chemical reaction / Synthesis. Use as a fuel. Shield gas for welding processes. Uses advised against : Do not inflate in party balloons because of the risk of explosion. Consumer use. 13. Details of the supplier of the safety data sheet/ Company identification : Eline Messer Lit Ateities g. 10 B-1 LT-08030 Vilnius - Lietuva www.elmemesser.iv vilnius @ elmemesser.iv vilnius @ elmemesser.iv 14. Emergency telephone number : Apsinuodijimų tamybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parq 5ECTION 2: Hazards identification : Apsinuodijimų tamybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parq	1.1. Product identifier	
Chemical description : hydrogen CAS-No. : 1333-74-0 EC-No. : 215-605-7 EC Index-No. : 001-001-00-9 Registration-No. : Listed in Annex IV / V REACH, exempted from registration. Chemical formula : H2 1.2. Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use. Test gas/Calibration gas. Laboratory use. Chemical reaction / Synthesis. Use as a fuel. Shield gas for welding processes. Use for manufacture of electronic/photovoltaic components. Laser gas. Contact supplier for more information on uses. Uses advised against : Do not inflate in party balloons because of the risk of explosion. Consumer use. 1.3. Details of the supplier of the safety data sheet Company identification : Elime Messer Lit Aterties g. 10 B-1 LT-08303 Vilnius - Lietuva www.elimemesser.lv vilnius@elimemesser.lv	Trade name	: hydrogen
CAS-No. : 1333-74-0 EC-No. : 215-605-7 EC Index-No. : 001-001-00-9 Registration-No. : Listed in Annex IV / V REACH, exempted from registration. Chemical formula : H2 12. Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use. Test gas/Calibration gas. Laboratory use. Chemical formula : Shield gas for welding processes. Use as a fuel. Shield gas for welding processes. Uses advised against : Do not inflate in party balloons because of the risk of explosion. Consumer use. Consumer use. 13. Details of the supplier of the safety data sheet Company identification Company identification : Elime Messer Lit Ateities g. 10 B-1 LT-08303 Vilnius - Lietuva www.elemenesser.lv vilnius @elemenesser.lv 14. Emergency telephone number : Apsinuodijimų tarrybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parq	SDS no	: LIT-H2-067A
EC-No.: 215-605-7 EC Index-No.: 001-001-00-9 Registration-No. : Listed in Annex IV / V REACH, exempted from registration. Chemical formula : H2 12. Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use. Test gas/Calibration gas. Laboratory use. Laboratory use. Chemical reaction / Synthesis. Use as a fuel. Shield gas for welding processes. Use for manufacture of electronic/photovoltaic components. Laser gas. Consumer use. Consumer use. 13. Details of the supplier of the safety data sheet Eleme Messer Lit Company identification : Eleme Messer Lit Ateities g.10 B-1 LT-08030 Vilnius - Lietuva www.elememesser.lv vilnius@elememesser.lv vilnius@elememesser.lv vilnius@elememesser.lv	Chemical description	: hydrogen
EC Index-No. : 001-001-00-9 Registration-No. : Listed in Annex IV / V REACH, exempted from registration. Chemical formula : H2 12. Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use. Test gas/Calibration gas. Laboratory use. Chemical reaction / Synthesis. Use as a fuel. Shield gas for welding processes. Use for manufacture of electronic/photovoltaic components. Laser gas. Contact supplier for more information on uses. Uses advised against : Do not inflate in party balloons because of the risk of explosion. Consumer use. 13. Details of the supplier of the safety data sheet Company identification : Elme Messer Lit Aterities g.10 B-1 LT-058303 Vinius - Lietuva www.elmemesser.lv vihius@elmemesser.lv vihius@elmemesser.lv		CAS-No. : 1333-74-0
Registration-No. : Listed in Annex IV / V REACH, exempted from registration. Chemical formula : H2 12. Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use. Test gas/Calibration gas. Laboratory use. Chemical reaction / Synthesis. Use as a fuel. Shield gas for welding processes. Use for manufacture of electronic/photovoltaic components. Laser gas. Contact supplier for more information on uses. Uses advised against : Do not inflate in party balloons because of the risk of explosion. Consumer use. 13. Details of the supplier of the safety data sheet Company identification : Elme Messer Lit Ateities g.10 B-1 LT-08303 Vinius - Lietuva www.elmemesser.lv 14. Emergency telephone number : Apsinuodijimų tamybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parq		EC-No. : 215-605-7
Chemical formula : H2 12. Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use. Test gas/Calibration gas. Laboratory use. Chemical reaction / Synthesis. Use as a fuel. Shield gas for welding processes. Uses for manufacture of electronic/photovoltaic components. Laser gas. Contact supplier for more information on uses. Uses advised against : Do not inflate in party balloons because of the risk of explosion. Consumer use. 13. Details of the supplier of the safety data sheet Company identification : Elme Messer Lit Ateities g. 10 B-1 LT-08303 Vilnius - Lietuva www.elmemesser.lv vilnius@elmemesser.lv 14. Emergency telephone number : Apsinuodijimų tamybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parq		EC Index-No. : 001-001-00-9
12. Relevant identified uses of the substance or nature and uses advised against Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use. Test gas/Calibration gas. Laboratory use. Chemical reaction / Synthesis. Use as a fuel. Shield gas for welding processes. Use for manufacture of electronic/photovoltaic components. Laser gas. Contact supplier for more information on uses. Uses advised against : Do not inflate in party balloons because of the risk of explosion. Consumer use. 13. Details of the supplier of the safety data sheet Company identification : Elme Messer Lit Ateities g. 10 B-1 LT-08303 Vilnius - Lietuva www.elmemesser.lv vilnius @elmemesser.lv 14. Emergency telephone number : Apsinuodijimų tarnybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parą	Registration-No.	: Listed in Annex IV / V REACH, exempted from registration.
Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use. Test gas/Calibration gas. Laboratory use. Laboratory use. Chemical reaction / Synthesis. Use as a fuel. Shield gas for welding processes. Use for manufacture of electronic/photovoltaic components. Laser gas. Contact supplier for more information on uses. : Do not inflate in party balloons because of the risk of explosion. Uses advised against : Do not inflate in party balloons because of the risk of explosion. Consumer use. : Elme Messer Lit Ateities g.10 B-1 LT-08303 Vilnius - Lietuva www.elmemesser.lv 14. Emergency telephone number : Apsinuodijimų tarnybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parą	Chemical formula	: H2
Test gas/Calibration gas. Laboratory use. Chemical reaction / Synthesis. Use as a fuel. Shield gas for welding processes. Use for manufacture of electronic/photovoltaic components. Laboratory use. Uses advised against : Do not inflate in party balloons because of the risk of explosion. Consumer use. 1.3. Details of the supplier of the safety data sheet Company identification : Elme Messer Lit Ateities g.10 B-1 LT-08303 Vilnius - Lietuva www.elmemesser.lv vilnius@elmemesser.lv vilnius@elmemesser.lv * : Apsinuodijimų tarnybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parą	1.2. Relevant identified uses of the substa	nce or mixture and uses advised against
Laboratory use. Chemical reaction / Synthesis. Use as a fuel. Shield gas for welding processes. Use for manufacture of electronic/photovoltaic components. Laser gas. Contact supplier for more information on uses. Energency telephone number 14. Emergency telephone number Emergency telephone number Fmergency telephone number : Apsinuodijimų tarnybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parą	Relevant identified uses	: Industrial and professional uses. Perform risk assessment prior to use.
Chemical reaction / Synthesis. Use as a fuel. Shield gas for welding processes. Use for manufacture of electronic/photovoltaic components. Laser gas. Contact supplier for more information on uses. Uses advised against : Do not inflate in party balloons because of the risk of explosion. Consumer use. : Do not inflate in party balloons because of the risk of explosion. Company identification : Elme Messer Lit Ateities g.10 B-1 LT-08303 Vilnius - Lietuva www.elmemesser.lv vilnius@elmemesser.lv 14. Emergency telephone number : Apsinuodijimų tarnybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parą		Test gas/Calibration gas.
Use as a fuel. Shield gas for welding processes. Use for manufacture of electronic/photovoltaic components. Laser gas. Contact supplier for more information on uses. E Do not inflate in party balloons because of the risk of explosion. Consumer use. Consumer use. 1.3. Details of the supplier of the safety data sheet E Elme Messer Lit Company identification : Elme Messer Lit A teities g.10 B-1 LT-08303 Vilnius - Lietuva www.elmemesser.lv vilnius @ elmemesser.lv vilnius @ elmemesser.lv is a pasinuodijimų tarnybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parą		Laboratory use.
Shield gas for welding processes. Use for manufacture of electronic/photovoltaic components. Laser gas. Contact supplier for more information on uses. Uses advised against : Do not inflate in party balloons because of the risk of explosion. Consumer use. 1.3. Details of the supplier of the safety data sheet Company identification : Elme Messer Lit Ateities g.10 B-1 LT-08303 Vilnius - Lietuva www.elmemesser.lv vilnius@elmemesser.lv 1.4. Emergency telephone number : Apsinuodijimų tarnybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parą		Chemical reaction / Synthesis.
Use for manufacture of electronic/photovoltaic components. Laser gas. Contact supplier for more information on uses. Uses advised against : Do not inflate in party balloons because of the risk of explosion. Consumer use. 1.3. Details of the supplier of the safety data sheet Company identification : Elme Messer Lit Ateities g.10 B-1 LT-08303 Vilnius - Lietuva www.elmemesser.lv 1.4. Emergency telephone number : Apsinuodijimų tarnybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parą		Use as a fuel.
Laser gas. Contact supplier for more information on uses. Uses advised against : Do not inflate in party balloons because of the risk of explosion. Consumer use. 1.3. Details of the supplier of the safety data sheet Company identification Company identification : Elme Messer Lit Ateities g.10 B-1 LT-08303 Vilnius - Lietuva www.elmemesser.lv vilnius@elmemesser.lv 1.4. Emergency telephone number : Apsinuodijimų tarnybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parą		Shield gas for welding processes.
Uses advised against Contact supplier for more information on uses. 1.3. Details of the supplier of the safety data sheet Company identification Company identification Elme Messer Lit Ateities g.10 B-1 LT-08303 Vilnius - Lietuva www.elmemesser.lv vilnius @elmemesser.lv 1.4. Emergency telephone number Apsinuodijimų tarnybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parą		Use for manufacture of electronic/photovoltaic components.
Uses advised against : Do not inflate in party balloons because of the risk of explosion. Consumer use. 1.3. Details of the supplier of the safety data sheet : Consumer use. Company identification : Elme Messer Lit Ateities g.10 B-1 LT-08303 Vilnius - Lietuva www.elmemesser.lv vilnius@elmemesser.lv 1.4. Emergency telephone number : Apsinuodijimų tarnybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parą		Laser gas.
Consumer use. 1.3. Details of the supplier of the safety data sheet Company identification : Elme Messer Lit Ateities g.10 B-1 LT-08303 Vilnius - Lietuva www.elmemesser.lv vilnius@elmemesser.lv 1.4. Emergency telephone number : Apsinuodijimų tarnybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parą		Contact supplier for more information on uses.
1.3. Details of the supplier of the safety data sheet Company identification : Elme Messer Lit Ateities g.10 B-1 LT-08303 Vilnius - Lietuva www.elmemesser.lv vilnius@elmemesser.lv 1.4. Emergency telephone number : Apsinuodijimų tarnybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parą	Uses advised against	: Do not inflate in party balloons because of the risk of explosion.
Company identification : Elme Messer Lit Ateities g.10 B-1 LT-08303 Vilnius - Lietuva www.elmemesser.lv vilnius@elmemesser.lv 1.4. Emergency telephone number : Apsinuodijimų tarnybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parą		Consumer use.
Ateities g.10 B-1 LT-08303 Vilnius - Lietuva www.elmemesser.lv vilnius@elmemesser.lv vilnius@elmemesser.lv tilnius@elmemesser.lv • Vilnius@elmemesser.lv	1.3. Details of the supplier of the safety da	ta sheet
LT-08303 Vilnius - Lietuva www.elmemesser.lv vilnius@elmemesser.lv 1.4. Emergency telephone number Emergency telephone number : Apsinuodijimų tarnybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parą	Company identification	
<u>www.elmemesser.lv</u> vilnius@elmemesser.lv <u>1.4. Emergency telephone number</u> Emergency telephone number : Apsinuodijimų tarnybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parą		
1.4. Emergency telephone number Emergency telephone number : Apsinuodijimų tarnybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parą		
Emergency telephone number : Apsinuodijimų tarnybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parą		vilnius@elmemesser.lv
Emergency telephone number : Apsinuodijimų tarnybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parą	1.4 Emergency telephone number	
		· Ansinuodiiimu tarnyhos nagalhos telefonas – ±370 5 236 20 52, 24 valandas per nara
SECTION 2: Hazards identification		. Apsindodijinių tarrybos pagaibos telefonas – 1570 5 250 20 52, 24 Valahuas per parą
	SECTION 2: Hazards identification	1

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]	
Physical hazards	Flam. Gas 1
	Press. Gas (Comp.)

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

H220 H280

ELME MESSER G44S	hydrogen
	SDS Ref.: LIT-H2-067A
Hazard pictograms (CLP)	: GHS02 GHS04
Signal word (CLP)	: Danger
Hazard statements (CLP)	: H220 - Extremely flammable gas. H280 - Contains gas under pressure; may explode if heated.
Precautionary statements (CLP)	
, , , , , , , , , , , , , , , , , , , ,	 Prevention : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	- Response : P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
	P381 - Eliminate all ignition sources if safe to do so.
	- Storage : P403 - Store in a well-ventilated place.
2.3. Other hazards	

: None.

SECTION 3: Composition/information on ingredients

3.1. Substances

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
hydrogen	(CAS-No.) 1333-74-0 (EC-No.) 215-605-7 (EC Index-No.) 001-001-00-9 (Registration-No.) *1	100	Flam. Gas 1, H220 Press. Gas (Comp.), H280

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

*3: Registration not required: Substance manufactured or imported < 1t/y.

3.2. Mixtures : Not applicable

SECTION 4: First aid measures

4.1. Description of first aid m	easures		
- Inhalation	 Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped. 		
- Skin contact	: Adverse effects not expected from this product.		
- Eye contact	: Adverse effects not expected from this product.		
- Ingestion	: Ingestion is not considered a potential route of exposure.		
4.2. Most important symptom	4.2. Most important symptoms and effects, both acute and delayed		
	 In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Refer to section 11. 		

ELME MESSER G/4/S

hydrogen

SDS Ref.: LIT-H2-067A

4.3. Indication of any immediate medical attention and special treatment needed

: None.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
- Suitable extinguishing media	: Water spray or fog. Dry powder.
- Unsuitable extinguishing media	: Do not use water jet to extinguish. Carbon dioxide.
5.2. Special hazards arising from the substa	nce or mixture
Specific hazards Hazardous combustion products	Exposure to fire may cause containers to rupture/explode.None.
5.3. Advice for firefighters	
Specific methods	: Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
	If possible, stop flow of product.
	Use water spray or fog to knock down fire fumes if possible.
	Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re- ignition may occur. Extinguish any other fire.
	Move containers away from the fire area if this can be done without risk.
Special protective equipment for fire fighters	: In confined space use self-contained breathing apparatus.
	Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.
	Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
	Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

: Try to stop release. Evacuate area. Monitor concentration of released product. Consider the risk of potentially explosive atmospheres. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Eliminate ignition sources. Ensure adequate air ventilation. Act in accordance with local emergency plan. Stay upwind. 6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

: Ventilate area.

: Try to stop release.

ELME MESSER G/4/AS

hydrogen

SDS Ref.: LIT-H2-067A

6.4. Reference to other sections

: See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	
Safe use of the product	: The product must be handled in accordance with good industrial hygiene and safety procedures.
	Only experienced and properly instructed persons should handle gases under pressure.
	Consider pressure relief device(s) in gas installations.
	Ensure the complete gas system was (or is regularily) checked for leaks before use.
	Do not smoke while handling product.
	Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
	Assess the risk of potentially explosive atmospheres and the need for explosion-proof equipment.
	Purge air from system before introducing gas.
	Take precautionary measures against static discharge.
	Keep away from ignition sources (including static discharges).
	Consider the use of only non-sparking tools.
	Do not breathe gas.
	Avoid release of product into work area.
	Ensure equipment is adequately earthed.
	Avoid suck back of water, acid and alkalis.
Safe handling of the gas receptacle	: Refer to supplier's container handling instructions.
	Do not allow backfeed into the container.
	Protect containers from physical damage; do not drag, roll, slide or drop.
	When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
	Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
	If user experiences any difficulty operating valve discontinue use and contact supplier.
	Never attempt to repair or modify container valves or safety relief devices.
	Damaged valves should be reported immediately to the supplier.
	Keep container valve outlets clean and free from contaminants particularly oil and water.
	Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
	Close container valve after each use and when empty, even if still connected to equipment.
	Never attempt to transfer gases from one cylinder/container to another.
	Never use direct flame or electrical heating devices to raise the pressure of a container.
	Do not remove or deface labels provided by the supplier for the identification of the content of the container.
	Suck back of water into the container must be prevented.
	Open valve slowly to avoid pressure shock.

7.2. Conditions for safe storage, including any incompatibilities

ELME MESSER GAAS	hydrogen
	SDS Ref.: LIT-H2-067
	: Observe all regulations and local requirements regarding storage of containers.
	Containers should not be stored in conditions likely to encourage corrosion.
	Container valve guards or caps should be in place.
	Containers should be stored in the vertical position and properly secured to prevent them from falling over.
	Stored containers should be periodically checked for general condition and leakage.
	Keep container below 50°C in a well ventilated place.
	Store containers in location free from fire risk and away from sources of heat and ignition.
	Keep away from combustible materials. Segregate from oxidant gases and other oxidants in store.
	All electrical equipment in the storage areas should be compatible with the risk of a potentially
	explosive atmosphere.
7.3. Specific end use(s)	
	: None.
SECTION 8: Exposure controls/per	rsonal protection
8.1. Control parameters	
OEL (Occupational Exposure Limits)	: None available.
OEL (Occupational Exposure Limits) DNEL (Derived-No Effect Level)	 None available. None available.
DNEL (Derived-No Effect Level)	: None available.
DNEL (Derived-No Effect Level) PNEC (Predicted No-Effect Concentration) 8.2. Exposure controls	: None available.
DNEL (Derived-No Effect Level) PNEC (Predicted No-Effect Concentration) 8.2. Exposure controls	: None available.
DNEL (Derived-No Effect Level) PNEC (Predicted No-Effect Concentration)	 None available. None available.
DNEL (Derived-No Effect Level) PNEC (Predicted No-Effect Concentration) 8.2. Exposure controls	 None available. None available. Provide adequate general and local exhaust ventilation.
DNEL (Derived-No Effect Level) PNEC (Predicted No-Effect Concentration) 8.2. Exposure controls	 None available. None available. Provide adequate general and local exhaust ventilation. Product to be handled in a closed system. Systems under pressure should be regularily checked for leakages. Gas detectors should be used when flammable gases/vapours may be released.
 DNEL (Derived-No Effect Level) PNEC (Predicted No-Effect Concentration) 8.2. Exposure controls 8.2.1. Appropriate engineering controls 	 None available. None available. Provide adequate general and local exhaust ventilation. Product to be handled in a closed system. Systems under pressure should be regularily checked for leakages. Gas detectors should be used when flammable gases/vapours may be released. Consider the use of a work permit system e.g. for maintenance activities.
DNEL (Derived-No Effect Level) PNEC (Predicted No-Effect Concentration) 8.2. Exposure controls	 None available. None available. Provide adequate general and local exhaust ventilation. Product to be handled in a closed system. Systems under pressure should be regularily checked for leakages. Gas detectors should be used when flammable gases/vapours may be released. Consider the use of a work permit system e.g. for maintenance activities.
 DNEL (Derived-No Effect Level) PNEC (Predicted No-Effect Concentration) 8.2. Exposure controls 8.2.1. Appropriate engineering controls 	 None available. None available. Provide adequate general and local exhaust ventilation. Product to be handled in a closed system. Systems under pressure should be regularily checked for leakages. Gas detectors should be used when flammable gases/vapours may be released. Consider the use of a work permit system e.g. for maintenance activities. Dersonal protective equipment
 DNEL (Derived-No Effect Level) PNEC (Predicted No-Effect Concentration) 8.2. Exposure controls 8.2.1. Appropriate engineering controls 	 None available. None available. Provide adequate general and local exhaust ventilation. Product to be handled in a closed system. Systems under pressure should be regularily checked for leakages. Gas detectors should be used when flammable gases/vapours may be released. Consider the use of a work permit system e.g. for maintenance activities. Dersonal protective equipment A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:
 DNEL (Derived-No Effect Level) PNEC (Predicted No-Effect Concentration) 8.2. Exposure controls 8.2.1. Appropriate engineering controls 	 None available. None available. Provide adequate general and local exhaust ventilation. Product to be handled in a closed system. Systems under pressure should be regularily checked for leakages. Gas detectors should be used when flammable gases/vapours may be released. Consider the use of a work permit system e.g. for maintenance activities. Dersonal protective equipment A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The
 DNEL (Derived-No Effect Level) PNEC (Predicted No-Effect Concentration) <u>8.2. Exposure controls</u> 8.2.1. Appropriate engineering controls 8.2.2. Individual protection measures, e.g. p 	 None available. None available. Provide adequate general and local exhaust ventilation. Product to be handled in a closed system. Systems under pressure should be regularily checked for leakages. Gas detectors should be used when flammable gases/vapours may be released. Consider the use of a work permit system e.g. for maintenance activities. Dersonal protective equipment A risk assessment should be conducted and documented in each work area to assess the risk related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:
 DNEL (Derived-No Effect Level) PNEC (Predicted No-Effect Concentration) <u>8.2. Exposure controls</u> 8.2.1. Appropriate engineering controls 8.2.2. Individual protection measures, e.g. p 	 None available. None available. Provide adequate general and local exhaust ventilation. Product to be handled in a closed system. Systems under pressure should be regularily checked for leakages. Gas detectors should be used when flammable gases/vapours may be released. Consider the use of a work permit system e.g. for maintenance activities. Dersonal protective equipment A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected.
 DNEL (Derived-No Effect Level) PNEC (Predicted No-Effect Concentration) 8.2. Exposure controls 8.2.1. Appropriate engineering controls 8.2.2. Individual protection measures, e.g. p • Eye/face protection 	 None available. None available. Provide adequate general and local exhaust ventilation. Product to be handled in a closed system. Systems under pressure should be regularily checked for leakages. Gas detectors should be used when flammable gases/vapours may be released. Consider the use of a work permit system e.g. for maintenance activities. Dersonal protective equipment A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected. Wear safety glasses with side shields.
 DNEL (Derived-No Effect Level) PNEC (Predicted No-Effect Concentration) 8.2. Exposure controls 8.2.1. Appropriate engineering controls 8.2.2. Individual protection measures, e.g. p Eye/face protection Skin protection 	 None available. None available. Provide adequate general and local exhaust ventilation. Product to be handled in a closed system. Systems under pressure should be regularily checked for leakages. Gas detectors should be used when flammable gases/vapours may be released. Consider the use of a work permit system e.g. for maintenance activities. Dersonal protective equipment A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected. Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specifications.
 DNEL (Derived-No Effect Level) PNEC (Predicted No-Effect Concentration) 8.2. Exposure controls 8.2.1. Appropriate engineering controls 8.2.2. Individual protection measures, e.g. p • Eye/face protection 	 None available. None available. Provide adequate general and local exhaust ventilation. Product to be handled in a closed system. Systems under pressure should be regularily checked for leakages. Gas detectors should be used when flammable gases/vapours may be released. Consider the use of a work permit system e.g. for maintenance activities. Dersonal protective equipment A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected. Wear safety glasses with side shields.
 DNEL (Derived-No Effect Level) PNEC (Predicted No-Effect Concentration) 8.2. Exposure controls 8.2.1. Appropriate engineering controls 8.2.2. Individual protection measures, e.g. p Eye/face protection Skin protection 	 None available. None available. Provide adequate general and local exhaust ventilation. Product to be handled in a closed system. Systems under pressure should be regularily checked for leakages. Gas detectors should be used when flammable gases/vapours may be released. Consider the use of a work permit system e.g. for maintenance activities. Dersonal protective equipment A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected. Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specifications. Wear working gloves when handling gas containers.
 DNEL (Derived-No Effect Level) PNEC (Predicted No-Effect Concentration) 8.2. Exposure controls 8.2.1. Appropriate engineering controls 8.2.2. Individual protection measures, e.g. p Eye/face protection Skin protection Hand protection 	 None available. None available. None available. Provide adequate general and local exhaust ventilation. Product to be handled in a closed system. Systems under pressure should be regularily checked for leakages. Gas detectors should be used when flammable gases/vapours may be released. Consider the use of a work permit system e.g. for maintenance activities. consider the use of a work permit system e.g. for maintenance activities. consider the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected. Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specifications. Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risk. Consider the use of flame resistant anti-static safety clothing. Standard EN 180 14116 - Limited flame spread materials.
 DNEL (Derived-No Effect Level) PNEC (Predicted No-Effect Concentration) 8.2. Exposure controls 8.2.1. Appropriate engineering controls 8.2.2. Individual protection measures, e.g. p Eye/face protection Skin protection Hand protection 	 None available. None available. Provide adequate general and local exhaust ventilation. Product to be handled in a closed system. Systems under pressure should be regularily checked for leakages. Gas detectors should be used when flammable gases/vapours may be released. Consider the use of a work permit system e.g. for maintenance activities. Dersonal protective equipment A risk assessment should be conducted and documented in each work area to assess the risk related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected. Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specifications. Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risk. Consider the use of flame resistant anti-static safety clothing.

Thermal hazards

Respiratory protection

EN (English)

: None necessary.

: None necessary.

hydrogen

SDS Ref.: LIT-H2-067A

8.2.3. Environmental exposure controls

 Specific risk management measures are not required beyond good industrial hygiene and safety procedures.
 Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

• Physical state at 20°C / 101.3kPa	: Gas
Colour	: Colourless.
Odour	: Odourless.
Odour threshold	: Odour threshold is subjective and inadequate to warn of overexposure.
рН	: Not applicable.
Melting point / Freezing point	: -259 °C
Boiling point	: -253 °C
Flash point	: Not applicable for gases and gas mixtures.
Evaporation rate	: Not applicable for gases and gas mixtures.
Flammability (solid, gas)	: Extremely flammable gas.
Explosive limits	[:] 4 - 77 vol %
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Vapour density	: Not applicable.
Relative density, liquid (water=1)	: 0.07
Relative density, gas (air=1)	: 0.07
Water solubility	: 1.6 mg/l
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for inorganic products.
Auto-ignition temperature	: 560 °C
Decomposition temperature	: Not applicable.
Viscosity	: Not applicable.
Explosive properties	: Not applicable.
Oxidising properties	: None.
9.2. Other information	
Molar mass	: 2 g/mol
Critical temperature [°C]	: -240 °C
Other data	: Burns with an invisible flame.

SECTION 10: Stability and reactivity

10.1. Reactivity	
	: No reactivity hazard other than the effects described in sub-sections below.
10.2. Chemical stability	. Ctable under normal and itigan
	: Stable under normal conditions.
10.3. Possibility of hazardous reactions	
	: May react violently with oxidants.
	Can form explosive mixture with air.

ELME MESSER GAAS	hydrogen
	SDS Ref.: LIT-H2-067A
10.4. Conditions to avoid	
	: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
	Avoid moisture in installation systems.
10.5. Incompatible materials	
	: Air, Oxidisers.
	For additional information on compatibility refer to ISO 11114.
10.6. Hazardous decomposition products	
	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
SECTION 11: Toxicological informa	ation

11.1. Information on toxicological effects		
Acute toxicity	: No known toxicological effects from this product.	
Skin corrosion/irritation	: No known effects from this product.	
Serious eye damage/irritation	: No known effects from this product.	
Respiratory or skin sensitisation	: No known effects from this product.	
Germ cell mutagenicity	: No known effects from this product.	
Carcinogenicity	: No known effects from this product.	
Toxic for reproduction : Fertility	: No known effects from this product.	
Toxic for reproduction : unborn child	: No known effects from this product.	
STOT-single exposure	: No known effects from this product.	
STOT-repeated exposure	: No known effects from this product.	
Aspiration hazard	: Not applicable for gases and gas mixtures.	

SECTION 12: Ecological information

12.1. Toxicity

Assessment	: No ecological damage caused by this product.
EC50 48h - Daphnia magna [mg/l] EC50 72h - Algae [mg/l] LC50 96 h - Fish [mg/l]	No data available.No data available.No data available.
12.2. Persistence and degradability	
Assessment	: No ecological damage caused by this product.
12.3. Bioaccumulative potential	
Assessment	: No ecological damage caused by this product.
<u>12.4. Mobility in soil</u>	
Assessment	: No ecological damage caused by this product.
12.5. Results of PBT and vPvB assessment	
Assessment	: Not classified as PBT or vPvB. No data available.

ELME MESSER GAAS	hydroge	١	
		SDS Ref.: LIT-H2	2-06
2.6. Other adverse effects			
Dther adverse effects	: No known effects from th	s product.	
Effect on the ozone layer	: None.		
Global warming potential [CO2=1]	: 6		
Effect on global warming	: No known effects from th	s product.	
SECTION 13: Disposal considerati	ions		
3.1. Waste treatment methods			
		as where there is a risk of forming an explosive mixture with air. ad through a suitable burner with flash back arrestor.	
	Do not discharge into any	place where its accumulation could be dangerous.	
		levels from local regulations or operating permits are not excee	ded
	Contact supplier if guidar		
		practice Doc.30 "Disposal of Gases", downloadable at re guidance on suitable disposal methods.	
		original container to supplier.	
ist of hazardous waste codes (from Commission Decision 2000/532/EC as Imended)		sure containers (including halons) containing hazardous substa	nce
3.2. Additional information			
	: None.		
	External treatment and di regulations.	sposal of waste should comply with applicable local and/or natio	onal
SECTION 14: Transport information	on		
14.1. UN number			
JN-No.	: 1049		
14.2. UN proper shipping name			
Fransport by road/rail (ADR/RID)	[:] HYDROGEN, COMPRES	SED	
Transport by air (ICAO-TI / IATA-DGR)	: HYDROGEN, COMPRES	SED	
ransport by sea (IMDG)	HYDROGEN, COMPRES	SED	
4.3. Transport hazard class(es)			
Labelling			
	2.1 : Flammable gases.		
Fransport by road/rail (ADR/RID)			
Class	: 2		
Classification code	: 1F		
lazard identification number	: 23		
Funnel Restriction		sage forbidden through tunnels of category B, C, D and E. Othe den through tunnels of category D and E	ər
Fransport by air (ICAO-TI / IATA-DGR)	camage . I assage forbid		
Class / Div. (Sub. risk(s))	: 2.1		
Fransport by sea (IMDG)			
Class / Div. (Sub. risk(s))	: 2.1		

ELME MESSER G/4/S

hydrogen

SDS Ref.: LIT-H2-067A

Emergency Schedule (EmS) - Fire	: F-D
Emergency Schedule (EmS) - Spillage	: S-U
14.4. Packing group	
Transport by road/rail (ADR/RID)	: Not applicable
Transport by air (ICAO-TI / IATA-DGR)	: Not applicable
Transport by sea (IMDG)	: Not applicable
14.5. Environmental hazards	
Transport by road/rail (ADR/RID)	: None.
Transport by air (ICAO-TI / IATA-DGR)	: None.
Transport by sea (IMDG)	: None.
<u>14.6. Special precautions for user</u> Packing Instruction(s)	
Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR)	: P200
Passenger and Cargo Aircraft	: Forbidden.
Cargo Aircraft only	: 200.
Transport by sea (IMDG)	: P200
Special transport precautions	 Avoid transport on vehicles where the load space is not separated from the driver's compartment.
	Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
	Before transporting product containers:
	- Ensure there is adequate ventilation.
	- Ensure that containers are firmly secured.
	- Ensure valve is closed and not leaking.
	- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
	- Ensure valve protection device (where provided) is correctly fitted.
14.7 Transport in bulk according to Annov	Lef Marriel and the IPC Code

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulat EU-Regulations	tions/legislation specific for the substance or mixture
Restrictions on use	: None.
Other information, restriction and prohibition regulations	: Ensure all national/local regulations are observed.
Seveso Directive : 2012/18/EU (Seveso III)	: Listed.
National regulations No additional information available	
15.2. Chemical safety assessment	
	: A CSA does not need to be carried out for this product.

ELME MESSER G/4/S

hydrogen

SECTION 16: Other information	۱
Indication of changes	: Revised safety data sheet in accordance with commission regulation (EU) No 2015/830.
Abbreviations and acronyms	: ATE - Acute Toxicity Estimate
	CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
	REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
	EINECS - European Inventory of Existing Commercial Chemical Substances
	CAS# - Chemical Abstract Service number
	PPE - Personal Protection Equipment
	LC50 - Lethal Concentration to 50 % of a test population
	RMM - Risk Management Measures
	PBT - Persistent, Bioaccumulative and Toxic
	vPvB - Very Persistent and Very Bioaccumulative
	STOT- SE : Specific Target Organ Toxicity - Single Exposure
	CSA - Chemical Safety Assessment
	EN - European Standard
	UN - United Nations
	ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
	IATA - International Air Transport Association
	IMDG code - International Maritime Dangerous Goods
	RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
	WGK - Water Hazard Class
	STOT - RE : Specific Target Organ Toxicity - Repeated Exposure
Training advice	: Ensure operators understand the flammability hazard.
	The hazard of asphyxiation is often overlooked and must be stressed during operator training.
DISCLAIMER OF LIABILITY	: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
	Details given in this document are believed to be correct at the time of going to press.
	Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.