Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ELME MESSER G/4/4S

OXYGEN Issue date: 03/06/2016 SDS reference: LIT-O2-097A

Supersedes: 01/07/2019

Revision date: 02/01/2020

Version: 3.2



Danger

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Trade name	: Oxygen, GOURMET O
SDS no	: LIT-O2-097A
Chemical description	: oxygen
	CAS-No.: 7782-44-7
	EC-No. : 231-956-9
	EC Index-No. : 008-001-00-8
Registration-No.	: Listed in Annex IV / V REACH, exempted from registration.
Chemical formula	: O2
	of the substance or mixture and uses advised against
Relevant identified uses	: Medical applications.
	Contact supplier for more information on uses.
	Welding, cutting, heating and brazing.
	Shield gas for welding processes.
	Use for manufacture of electronic/photovoltaic components.
	Water treatment.
	Laser gas.
	Laboratory use.
	Food applications.
	Industrial and professional uses. Perform risk assessment prior to use.
	Test gas/Calibration gas.
Uses advised against	: Consumer use.
	Attention: These products must not be applied to humans or animals unless they are expressly designated as medical or medicinal gases!.
1.3. Details of the supplier of	the safety data sheet
Company identification	: Elme Messer Lit
Company Identification	Ateities g.10 B-1
	LT-08303 Vilnius - Lietuva
	www.elmemesser.lv vilnius@elmemesser.lv
	Virtus@einemessel.iv
1.4. Emergency telephone nu	Imber
Emergency telephone number	: Apsinuodijimų tarnybos pagalbos telefonas – +370 5 236 20 52, 24 valandas per parą
	. Apsindodijinių tarrybos pagabos teletonas – 1970 5 250 20 52, 24 valandas per parą
SECTION 2: Hazards id	entification
2.1. Classification of the sub	stance or mixture
Classification according to R	Regulation (EC) No. 1272/2008 [CLP]
Physical hazards	Ox. Gas 1 H270
	Press. Gas (Comp.) H280

ELME MESSER G44S		oxygen	
			SDS Ref.: LIT-O2-097A
2.2. Label elements			
Labelling according to Regulat	ion (EC) No. 127	2/2008 [CLP]	
Hazard pictograms (CLP)	:	GHS03 GHS04	
Signal word (CLP)	:	Danger	
Hazard statements (CLP)	:	H270 - May cause or intensify fire; oxidiser.	
		H280 - Contains gas under pressure; may explode if heated.	
Precautionary statements (CLP)		H280 - Contains gas under pressure; may explode if heated.	
Precautionary statements (CLP)	- Prevention :	H280 - Contains gas under pressure; may explode if heated. P220 - Keep away from combustible materials.	
Precautionary statements (CLP)	- Prevention :		
Precautionary statements (CLP)		P220 - Keep away from combustible materials.	

2.3. Other hazards

: None.

SECTION 3: Composition/information on ingredients

3.1. Substances

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
oxygen	(CAS-No.) 7782-44-7 (EC-No.) 231-956-9 (EC Index-No.) 008-001-00-8 (Registration-No.) *1	100	Ox. Gas 1, H270 Press. Gas (Comp.), H280

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

*3: Registration not required: Substance manufactured or imported < 1t/y.

3.2. Mixtures : Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation

- Skin contact
- Eye contact
- Ingestion

- : Remove victim to uncontaminated area.
- : Adverse effects not expected from this product.
- : Adverse effects not expected from this product. : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

ELME MESSER G/4/S

oxygen

SDS Ref.: LIT-O2-097A

: Continuous inhalation of concentrations higher than 75% may cause nausea, dizziness, respiratory difficulty and convulsion. Refer to section 11.

4.3. Indication of any immediate medical attention and special treatment needed

: None.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media - Unsuitable extinguishing media	: Water spray or fog. : Do not use water jet to extinguish.
5.2. Special hazards arising from the subst	
Specific hazards	: Exposure to fire may cause containers to rupture/explode. Supports combustion.
Hazardous combustion products	: None.
5.3. Advice for firefighters	
Specific methods	: Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
	If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible.
Special protective equipment for fire fighters	Move containers away from the fire area if this can be done without risk. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.
	Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
	Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

:	Try to stop release.
	Evacuate area.
	Monitor concentration of released product.
	Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.
	Eliminate ignition sources.
	Ensure adequate air ventilation.
	Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
	Act in accordance with local emergency plan.
	Stay upwind.
6.2. Environmental precautions	
:	Try to stop release.
6.3. Methods and material for containment and	cleaning up
:	: Ventilate area.
6.4. Reference to other sections	

ELME MESSER G/4/S

SECTION 7: Handling and storage

oxygen

SDS Ref.: LIT-O2-097A

: See also sections 8 and 13.

Safe use of the product	: The product must be handled in accordance with good industrial hygiene and safety
	procedures.
	Only experienced and properly instructed persons should handle gases under pressure.
	Consult supplier for specific recommendations.
	Consider pressure relief device(s) in gas installations.
	Ensure the complete gas system was (or is regularily) checked for leaks before use.
	Do not smoke while handling product.
	Use no oil or grease.
	Use only properly specified equipment which is suitable for this product, its supply pressure an temperature. Contact your gas supplier if in doubt.
	Use only oxygen approved lubricants and oxygen approved sealings.
	Use only with equipment cleaned for oxygen service and rated for container pressure.
	Do not breathe gas.
	Avoid release of product into work area.
	Keep equipment free from oil and grease. For more guidance, refer to the EIGA Doc. 33 - Cleaning of Equipment for Oxygen Service downloadable at http://www.eiga.eu.
	Avoid suck back of water, acid and alkalis.
Safe handling of the gas receptacle	: Refer to supplier's container handling instructions.
	Do not allow backfeed into the container.
	Protect containers from physical damage; do not drag, roll, slide or drop.
	When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
	Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
	If user experiences any difficulty operating valve discontinue use and contact supplier.
	Never attempt to repair or modify container valves or safety relief devices.
	Damaged valves should be reported immediately to the supplier.
	Keep container valve outlets clean and free from contaminants particularly oil and water.
	Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
	Close container valve after each use and when empty, even if still connected to equipment.
	Never attempt to transfer gases from one cylinder/container to another.
	Never use direct flame or electrical heating devices to raise the pressure of a container.
	Do not remove or deface labels provided by the supplier for the identification of the content of the container.
	Suck back of water into the container must be prevented.
	Open valve slowly to avoid pressure shock.

7.2. Conditions for safe storage, including any incompatibilities

	oxygen
	SDS Ref.: LIT-O2-09
	: Observe all regulations and local requirements regarding storage of containers.
	Containers should not be stored in conditions likely to encourage corrosion.
	Container valve guards or caps should be in place.
	Containers should be stored in the vertical position and properly secured to prevent them from falling over.
	Stored containers should be periodically checked for general condition and leakage.
	Keep container below 50°C in a well ventilated place.
	Segregate from flammable gases and other flammable materials in store.
	Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.
	Reep away non compusible materials.
7.3. Specific end use(s)	
	: None.
SECTION 8: Exposure controls/per	rsonal protection
8.1. Control parameters	
OEL (Occupational Exposure Limits)	: None available.
DNEL (Derived-No Effect Level)	: None available.
PNEC (Predicted No-Effect Concentration)	: None available.
3.2. Exposure controls	
8.2.1. Appropriate engineering controls	: Provide adequate general and local exhaust ventilation.
	. Trovido ddoquddo goriordi dila loodi oxirador voriniation.
	Systems under pressure should be regularily checked for leakages.
	Systems under pressure should be regularily checked for leakages. Avoid oxygen rich (>23,5%) atmospheres.
	Avoid oxygen rich (>23,5%) atmospheres. Gas detectors should be used when oxidising gases may be released. Consider the use of a work permit system e.g. for maintenance activities.
8.2.2. Individual protection measures, e.g. p	Avoid oxygen rich (>23,5%) atmospheres. Gas detectors should be used when oxidising gases may be released. Consider the use of a work permit system e.g. for maintenance activities. personal protective equipment
8.2.2. Individual protection measures, e.g. p	Avoid oxygen rich (>23,5%) atmospheres. Gas detectors should be used when oxidising gases may be released. Consider the use of a work permit system e.g. for maintenance activities. personal protective equipment
	 Avoid oxygen rich (>23,5%) atmospheres. Gas detectors should be used when oxidising gases may be released. Consider the use of a work permit system e.g. for maintenance activities. personal protective equipment A risk assessment should be conducted and documented in each work area to assess the risl related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected. Wear suitable hand, body and head protection. Wear goggles with suitable filter lenses when
• Eye/face protection	 Avoid oxygen rich (>23,5%) atmospheres. Gas detectors should be used when oxidising gases may be released. Consider the use of a work permit system e.g. for maintenance activities. personal protective equipment A risk assessment should be conducted and documented in each work area to assess the risl related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected. Wear suitable hand, body and head protection. Wear goggles with suitable filter lenses when use is cutting/welding. Wear safety glasses with side shields.
• Eye/face protection	 Avoid oxygen rich (>23,5%) atmospheres. Gas detectors should be used when oxidising gases may be released. Consider the use of a work permit system e.g. for maintenance activities. personal protective equipment A risk assessment should be conducted and documented in each work area to assess the risk related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected. Wear suitable hand, body and head protection. Wear goggles with suitable filter lenses when use is cutting/welding. Wear safety glasses with side shields.
• Eye/face protection • Skin protection	 Avoid oxygen rich (>23,5%) atmospheres. Gas detectors should be used when oxidising gases may be released. Consider the use of a work permit system e.g. for maintenance activities. personal protective equipment A risk assessment should be conducted and documented in each work area to assess the risk related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected. Wear suitable hand, body and head protection. Wear goggles with suitable filter lenses when use is cutting/welding. Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specifications.
• Eye/face protection • Skin protection	 Avoid oxygen rich (>23,5%) atmospheres. Gas detectors should be used when oxidising gases may be released. Consider the use of a work permit system e.g. for maintenance activities. personal protective equipment A risk assessment should be conducted and documented in each work area to assess the risl related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected. Wear suitable hand, body and head protection. Wear goggles with suitable filter lenses when use is cutting/welding. Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specifications.
Eye/face protection Skin protection - Hand protection	 Avoid oxygen rich (>23,5%) atmospheres. Gas detectors should be used when oxidising gases may be released. Consider the use of a work permit system e.g. for maintenance activities. personal protective equipment A risk assessment should be conducted and documented in each work area to assess the risk related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected. Wear suitable hand, body and head protection. Wear goggles with suitable filter lenses when use is cutting/welding. Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specifications. Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risk. Consider the use of flame resistant safety clothing. Standard EN ISO 14116 - Limited flame spread materials. Wear safety shoes while handling containers.

Elme Messer Lit Ateities g.10 B-1 LT-08303 Vilnius Lietuva

oxygen

SDS Ref.: LIT-O2-097A

: None necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

rippourunoe	
Physical state at 20°C / 101.3kPa	: Gas
• Colour	: Colourless.
Odour	: No odour warning properties.
Odour threshold	: Odour threshold is subjective and inadequate to warn of overexposure.
рН	: Not applicable.
Melting point / Freezing point	: -219 °C
Boiling point	: -183 °C
Flash point	: Not applicable for gases and gas mixtures.
Evaporation rate	: Not applicable for gases and gas mixtures.
Flammability (solid, gas)	: Non flammable.
Explosive limits	[:] Non flammable.
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Vapour density	: Not applicable.
Relative density, liquid (water=1)	: 1.1
Relative density, gas (air=1)	: 1.1
Water solubility	: 39 mg/l
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for inorganic products.
Auto-ignition temperature	: Not applicable.
Decomposition temperature	: Not applicable.
Viscosity	: Not applicable.
Explosive properties	: Not applicable.
Oxidising properties	: Oxidiser.
9.2. Other information	
Molar mass	: 32 g/mol
Critical temperature [°C]	: -118 °C
- Coefficient of oxygen equivalency (Ci)	: 1
Other data	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.
	g

SECTION 10: Stability and reactivity

10.1. Reactivity	
	: No reactivity hazard other than the effects described in sub-sections below.
10.2. Chemical stability	
	: Stable under normal conditions.
10.3 Possibility of bazardous reactions	
Toto: Tossisinty of hazardous reactions	· Violently oxidises organic material
10.4. Conditions to avoid	
10.3. Possibility of hazardous reactions 10.4. Conditions to avoid	Stable under normal conditions.Violently oxidises organic material.

ELME MESSER G44S	oxygen
	SDS Ref.: LIT-02-097A
	SDS Ref.: L11-02-09/A
	: None under recommended storage and handling conditions (see section 7). Avoid moisture in installation systems.
10.5. Incompatible materials	
	: May react violently with reducing agents.
	May react violently with combustible materials.
	Keep equipment free from oil and grease. For more guidance, refer to the EIGA Doc. 33 - Cleaning of Equipment for Oxygen Service downloadable at http://www.eiga.eu. Consider the potential toxicity hazard due to the presence of chlorinated or fluorinated polymers
	in high pressure (> 30 bar) oxygen lines in case of combustion.
	For additional information on compatibility refer to ISO 11114.
10.6. Hazardous decomposition products	
	: None.
SECTION 11: Toxicological inforn	nation
11.1. Information on toxicological effects	
Acute toxicity	: No known toxicological effects from this product.
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas mixtures.
SECTION 12: Ecological informati	ion
_	
12.1. Toxicity	
Assessment	: No ecological damage caused by this product.
EC50 48h - Daphnia magna [mg/l]	: No data available.
EC50 72h - Algae [mg/l]	: No data available.

LC50 96 h - Fish [mg/l] : No data available.

12.2. Persistence and degradability

Assessment

12.3. Bioaccumulative potential

Assessment

12.4. Mobility in soil

Assessment

: No ecological damage caused by this product.

: No ecological damage caused by this product.

: No ecological damage caused by this product.

12.5. Results of PBT and vPvB assessment

ELME MESSER GAAS	oxygen
	SDS Ref.: LIT-O2-097A
Assessment	: Not classified as PBT or vPvB. No data available.
12.6. Other adverse effects	
Other adverse effects	: No known effects from this product.
Effect on the ozone layer	: None.
Effect on global warming	: None.
SECTION 13: Disposal considera	tions
	Contact supplier if guidance is required.
	Do not discharge into any place where its accumulation could be dangerous.
	Ensure that the emission levels from local regulations or operating permits are not exceeded.
	Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at http://www.eiga.eu for more guidance on suitable disposal methods.
	May be vented to atmosphere in a well ventilated place.
	Return unused product in original container to supplier.
List of hazardous waste codes (from Commission Decision 2000/532/EC as amended)	: 16 05 04 *: Gases in pressure containers (including halons) containing hazardous substances.
13.2. Additional information	
	: None.
	External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information

14.1. UN number	
UN-No.	: 1072
14.2. UN proper shipping name	
Transport by road/rail (ADR/RID)	[:] OXYGEN, COMPRESSED
Transport by air (ICAO-TI / IATA-DGR)	[:] OXYGEN, COMPRESSED
Transport by sea (IMDG)	COMPRESSED
14.3. Transport hazard class(es)	
Labelling	
	2.2 : Non flammable, non-toxic gases.
	5.1 : Oxidizing substances.
Transport by road/rail (ADR/RID)	
Class	: 2
Classification code	: 10
Hazard identification number	: 25
Tunnel Restriction	: E - Passage forbidden through tunnels of category E
Transport by air (ICAO-TI / IATA-DGR)	
Class / Div. (Sub. risk(s))	: 2.2 (5.1)

ELME MESSER G/4/IS

oxygen

SDS Ref.: LIT-O2-097A

Transport by sea (IMDG)	
Class / Div. (Sub. risk(s))	: 2.2 (5.1)
Emergency Schedule (EmS) - Fire	: F-C
Emergency Schedule (EmS) - Spillage	: S-W
14.4. Packing group	
Transport by road/rail (ADR/RID)	: Not applicable
Transport by air (ICAO-TI / IATA-DGR)	: Not applicable
Transport by sea (IMDG)	: Not applicable
14.5. Environmental hazards	
Transport by road/rail (ADR/RID)	: None.
Transport by air (ICAO-TI / IATA-DGR)	: None.
Transport by sea (IMDG)	: None.
14.6. Special precautions for user Packing Instruction(s) Transport by road/rail (ADR/RID)	: P200
Transport by air (ICAO-TI / IATA-DGR)	200
Passenger and Cargo Aircraft	: 200.
Cargo Aircraft only	: 200.
Transport by sea (IMDG)	: P200
Special transport precautions	: Avoid transport on vehicles where the load space is not separated from the driver's compartment.
	Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
	Before transporting product containers:
	- Ensure there is adequate ventilation.
	- Ensure that containers are firmly secured.
	- Ensure valve is closed and not leaking.
	- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
	- Ensure valve protection device (where provided) is correctly fitted.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Restrictions on use	: None.
Other information, restriction and prohibition regulations	: Ensure all national/local regulations are observed.
Seveso Directive : 2012/18/EU (Seveso III)	: Listed.
National regulations	

No additional information available

ELME MESSER GAAS

oxygen

15.2. Chemical safety assessment

: A CSA does not need to be carried out for this product.

SECTION 16: Other informati	
Indication of changes	: Revised safety data sheet in accordance with commission regulation (EU) No 2015/830.
Abbreviations and acronyms	: ATE - Acute Toxicity Estimate
	CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
	REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
	EINECS - European Inventory of Existing Commercial Chemical Substances
	CAS# - Chemical Abstract Service number
	LC50 - Lethal Concentration to 50 % of a test population
	RMM - Risk Management Measures
	PBT - Persistent, Bioaccumulative and Toxic
	vPvB - Very Persistent and Very Bioaccumulative
	STOT- SE : Specific Target Organ Toxicity - Single Exposure
	CSA - Chemical Safety Assessment
	EN - European Standard
	UN - United Nations
	ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
	IATA - International Air Transport Association
	IMDG code - International Maritime Dangerous Goods
	RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
	WGK - Water Hazard Class
	STOT - RE : Specific Target Organ Toxicity - Repeated Exposure
Training advice	: Ensure operators understand the hazard of oxygen enrichment.
DISCLAIMER OF LIABILITY	: Before using this product in any new process or experiment, a thorough material compatibility
	and safety study should be carried out.
	Details given in this document are believed to be correct at the time of going to press.
	Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.